



SAFETY DATA SHEET

Graffiti Remover

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME Graffiti Remover
PRODUCT NO. 19045
SUPPLIER Premiere Products
Oakley Gardens,
Bouncers Lane,
Cheltenham, GLOS GL52 5JD
01242 537103
01242 537177
Fax - 01242 528445
laboratory@premiereproducts.co.uk

2 HAZARDS IDENTIFICATION

Extremely flammable. Irritating to eyes and skin.

CLASSIFICATION Xi;R36/38. F+;R12.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTANE	203-448-7	106-97-8	31-35	F+;R12
N-METHYL-2-PYRROLIDONE	212-828-1	872-50-4	10-30%	Xi;R36/38
PROPAN-2-OL	200-661-7	67-63-0	10-30%	F;R11 Xi;R36 R67

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. Get medical attention.

INGESTION

Rinse mouth thoroughly. Promptly get affected person to drink large volumes of water to dilute the swallowed chemical. DO NOT INDUCE VOMITING! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention immediately!

SKIN CONTACT

Promptly flush contaminated skin with water. Promptly remove clothing if soaked through and flush the skin with water. Get medical attention if irritation persists after washing.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Carbon dioxide (CO2).

SPECIAL FIRE FIGHTING PROCEDURES

Be aware of danger of explosion. Use pressurised air mask if product is involved in a fire.

UNUSUAL FIRE & EXPLOSION HAZARDS

May explode when heated or when exposed to flames or sparks. Aerosol cans may explode in a fire.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

Graffiti Remover

PERSONAL PRECAUTIONS

Use protective gloves, goggles and suitable protective clothing.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground. Contain spillages with sand, earth or any suitable adsorbent material.

SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Read and follow manufacturer's recommendations.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Store in tightly closed original container in a dry and cool place.

STORAGE CLASS

Chemical storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
N-METHYL-2-PYRROLIDONE	WEL	25 ppm(Sk)	103 mg/m3(Sk)	75 ppm(Sk)	309 mg/m3(Sk)	
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT



RESPIRATORY EQUIPMENT

Respiratory protection must be used if air contamination exceeds acceptable level. If ventilation is insufficient, suitable respiratory protection must be provided.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Use approved safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Colourless		
ODOUR	Solvent.		
SOLUBILITY	Slightly soluble in water.		
BULK DENSITY	0.75	VISCOSITY	<10 cps 20

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

11 TOXICOLOGICAL INFORMATION

Graffiti Remover

INHALATION

Vapour from this chemical can be hazardous when inhaled.

INGESTION

May cause stomach pain or vomiting. May cause severe internal injury.

SKIN CONTACT

Prolonged contact may cause dryness of the skin. Irritating to skin.

EYE CONTACT

Irritating to eyes. May cause severe irritation to eyes.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

DEGRADABILITY

The product is biodegradable.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

UN NO. ROAD	1950	IMDG CLASS	2
IMDG PACK GR.	II	AIR CLASS	2

15 REGULATORY INFORMATION

LABELLING



Irritant



Extremely Flammable

RISK PHRASES

R12	Extremely flammable.
R36/38	Irritating to eyes and skin.

SAFETY PHRASES

S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.
S60	This material and its container must be disposed of as hazardous waste.

16 OTHER INFORMATION

SDS NO.	7
DATE	11/09

Graffiti Remover

RISK PHRASES IN FULL

R11	Highly flammable.
R12	Extremely flammable.
R36	Irritating to eyes.
R36/38	Irritating to eyes and skin.
R67	Vapours may cause drowsiness and dizziness.